

AIR OPERATED LOCKING DIFFERENTIAL

RD24

Nissan H233B,33 SPL**

**THIS MODEL WAS SUPERSEDED BY RD135, CROSSED OUT PARTS NOT AVAILABLE

PARTS LIST				
ITEM #	QTY	DESCRIPTION	PART#	NOTES
01	1	FLANGE CAP	020302	
02	1	CLUTCH GEAR	050202	
03	1	DIFFERENTIAL CASE	010307	
04	1	RETURN SPRINGS (PK OF 4)	150101SP	
05	1	RETAINING PIN SET (PK OF 4)	120303SP	
06	4	SHORT CROSS SHAFT	060402	
07	1	PISTON	040202SP	
08	1	BONDED SEAL	160705SP	
09	1	CYLINDER CAP ASSEMBLY	030214	
10	1	CYL CAP RETAINING BOLT (PK OF 8)	200205SP	
11	1	LOCKING TAB (8mm) (PK OF 8)	150401SP	
12	1	TAPERED ROLLER BEARING	NOT SUPPLIED	
13	1	ADJUSTER NUT	100102SP	
14	1	SEAL HOUSING KIT	081902SP	
15	1	SEAL HOUSING O-RINGS (PK OF 2)	160235SP	1
16	1	SEAL HOUSING RETAINING CLIP	150601SP	
17	1	SPLINED SIDE GEAR	SEE NOTE	3
18	1	PINION THRUST WASHER (PK OF 4)	151102SP	
19	4	PINION GEAR	SEE NOTE	3
20	1	SPIDER BLOCK	070201SP	
21	1	SIDE GEAR	SEE NOTE	3
22	1	S GEAR THRUST WASHER (PK OF 2)	151002SP	
*	9	RING GEAR BOLT SPACER	4581061	2
*	1	BULKHEAD FITTING KIT (O-RING TYPE)	170111	
*	1	PUSH-IN FITTING (5mm to 1/8"BSPP)	170201SP	
*	1	AIR LINE (5mm DIA X 6m LONG)	170301SP	
*	1	SOLENOID VALVE (12V)	180103	
*	1	SWITCH	180209SP	
*	1	SWITCH COVER (REAR)	180211SP	
*	1	CABLE TIE (PK OF 25)	180305	
*	1	OPERATING & SERVICE MANUAL	210200	
*	1	INSTALLATION GUIDE	210224	

^{*} Not illustrated in exploded view

NOTES

- 1 For replacement O-rings use only BS133 Viton 75.
- 2 If ring gear bolts are 10mm then spacers must be used (supplied with kit).
- 3 Available only as complete 6 gear set # 728A031
- For information on RD24 models with metal pistons, contact ARB.
- For seal housing set-up refer to tech notes (Section 5.1 & 5.2).








RD24

Nissan H233B,33 SPL**

**THIS MODEL WAS SUPERSEDED BY RD135, CROSSED OUT PARTS NOT AVAILABLE



SPECIFICATIONS

Axle Spline 33 tooth, Ø33.3mm [1.31"]

Ratio Supported All

Ring Gear ID 146.0mm [5.75"]

Ring Gear Bolts 9 bolts on Ø176mm [6.93"]

Ring Gear Bolt Size 12mm

Ring Gear Torque 142Nm [105 ft-lb]

Backlash 0.15-0.20mm [0.006-0.008"]

Bearing Cap Torque 99Nm [73 ft-lb]